

Pipe Information Tables

COIL FOOTAGE PER WRAP SINGLE WALL PIPE*														
Pipe Diameter - Roll Footage	1st Wrap	2nd Wrap	3rd Wrap	4th Wrap	5th Wrap	6th Wrap	7th Wrap	8th Wrap	9th Wrap	10th Wrap	11th Wrap	12th Wrap	13th Wrap	Total Footage
3" - 5,500'	169	210	250	300	340	385	425	470	511	550	590	630	670	5,500
Total footage		379	629	929	1,269	1,654	2,079	2,549	3,060	3,610	4,200	4,830	5,500	
4" - 3,200'	131	147	222	236	297	334	393	434	473	533				3,200
Total footage		278	500	736	1,033	1,267	1,760	2,194	2,667	3,200				
5" - 2,000'	125	155	200	228	274	304	342	372						2,000
Total footage		280	480	708	982	1,286	1,628	2,000						
6" - 1,500'	88	121	183	218	245	285	360							1,500
Total footage		209	392	610	855	1,140	1,500							
8" - 720'	72	110	148	175	215									720
Total footage		182	330	505	720									
10" - 520'	77	101	144	198										520
Total footage		178	322	520										
12" - 330'	60	115	155											330
Total footage		175	330											

DRAINAGE PIPE REQUIREMENTS PER ACRE (LATERALS)**	
Spacing (between pipe)	Pipe Per Acre (estimated)
20' (6.1 m)	2,200' (671 m)
30' (9.1 m)	1,450' (442 m)
40' (12.2 m)	1,100' (335 m)
50' (15.2 m)	900' (274 m)
60' (18.3 m)	725' (221 m)
70' (21.3 m)	638' (194 m)
80' (24.4 m)	550' (168 m)
90' (27.4 m)	500' (152 m)
100' (30.5 m)	450' (137 m)
150' (45.7 m)	338' (103 m)
200' (61.0 m)	225' (69 m)
250' (76.2 m)	188' (57 m)
300' (91.4 m)	150' (46 m)

** Table refers to single wall pipe, which is shown in more detail on page 11.

DUAL WALL PIPE TRUCK LOAD CHART*** MAXIMUM LINEAR FOOT PER LOAD		
Pipe Diameter	10' (3.0 m) Pipe Length	20' (6.1 m) Pipe Length
12" (300 mm)	2,580' (786 m)	2,400' (731 m)
15" (375 mm)	1,700' (518 m)	1,600' (487 m)
18" (450 mm)	1,200' (366 m)	1,120' (341 m)
24" (600 mm)	630' (192 m)	600' (182 m)
30" (750 mm)	360' (110 m)	360' (110 m)
36" (900 mm)	240' (73 m)	240' (73 m)
42" (1050 mm)	200' (61 m)	200' (61 m)
48" (1200 mm)	120' (36 m)	120' (36 m)
60" (1500 mm)	80' (24 m)	80' (24 m)

*** Table refers to N-12" dual wall stick pipe, which is shown in more detail on page 13.

8" - 15" DUAL WALL FLEX PIPE****	
DIAMETER	STANDARD LENGTHS
8" (200 mm)	920' (280.4 m) Solid
	920' (280.4 m) Perf
	920' (280.4 m) Fine Slot
10" (250 mm)	550' (167.6 m) Solid
	550' (167.6 m) Fine Slot
12" (300 mm)	360' (109.7 m) Solid
	360' (109.7 m) Perf
	360' (109.7 m) Fine Slot
15" (375 mm)	165' (50.3 m) Solid
	165' (50.3 m) Perf
	165' (50.3 m) Fine Slot

****Table refers to N-12" FLEX pipe, which is shown in more detail on page 12.